






## K 22



### K 22



				
	mm	mm	kg/m	mm
	250	15,0	4,39	

### BESCHREIBUNG

- Längsorientiertes Profil mit geschlossenen Schultern
- Antriebsachsen von Reise-, Stadtbussen und LKW
- Bereifung für Auflieger, Anhänger, Nachlauf- und Lenkachsen
- Einsatz im Nah- und Fernverkehr
- Richtungsstabil
- Durch ausgeprägte Querlamellierung gute Traktionseigenschaften auf trockener und nasser Fahrbahn
- Laufruhig
- Gute Laufleistung

### ALTERNATIVEN

Stadtbusse:	K27, K28
Überland- und Reisebusse:	K25, K27
Nah- und Fernverkehr:	K25, K27
Gemischter Einsatz:	K25

### FEATURES

- Longitudinal tread with closed shoulders
- Drive axle tire for inter-city busses, city busses and trucks
- Tires for semi-trailer, trailer and trailing axles
- For use on short and long distance
- Straight-running stability
- Good traction properties on wet and dry surfaces due to marked transversal sipes
- Smooth running
- Good running properties

### ALTERNATIVES

City busses:	K27, K28
Tourist and inter-city busses:	K25, K27
Short and long distances:	K25, K27
Varied use:	K25